



EXCLUSIVE AUTOMOTIVE PRODUCTS

**SEAT FITTING INSTRUCTION AUTOTECNICA SEATS
REPLACEMENT SEAT ADAPTOR / PART NO: 671 (L&R) Hi-LUX 97-05**

PLEASE READ THE INSTRUCTION IN FULL BEFORE FITTING AUTOTECNICA SEATS TO THE VEHICLE.

1. Park the vehicle and ensure the hand brake is on.
Remove the seat from the vehicle and retain the bolts removed when refitting the new seat.
If the seat has a seat belt attached please remove the seat belt from the seat to be attached to the provided anchorage point onto the new adaptor with supplied bolt.
2. Place the new Autotecnica seat upside down in a suitable position and place the 4 supplied washes on the seat mounting holes. "**Photo (A)**"

Photo (A)



Contents:

4 X 3MMX22MM WASHERS
4 X 30MM M8 BOLTS
4 X SPRING WASHERS
1 X SEAT BELT
NUT/BOLT/WASHERS.

3. Insert the "U" shaped handle onto the locating pins of the adaptor. *Please wedge in a flathead screwdriver when fitting the "U" shaped handle onto the pins. Place the assembled adaptor onto the seat ensuring the seat mounting holes line up with the adaptor bolt holes. See "**Photo (B)** **Note: Only if the adaptor is not assembled.**"
 - Starting from the back of the seat using the supplied bolts and washers to attach the adaptor/slider onto the seat.
 - Secure the bolts but do not tighten them.
4. Using the adjusting lever "U shape" move the seat adaptor frontwards to locate the other two mounting holes. Place and secure the bolts to the other two mounting holes. Securely all bolts correctly "**Photo (C)**"

Photo (B)



*For an easier fitment, wedge in a flat head screw driver between the track and handle to slide and position the "U shape" handle over the locating pins

Photo (C)



5. Place the assembled seat onto the original seat mounting holes by using the 4 original bolts and washers. In some vehicles, larger washes are needed. Washes not supplied. Tighten all bolts to correct manufacturer tension.* Attach the removed seat belt to the adaptor seat belt bracket with the provided bolt and nut/washers and secure correctly.



All Images used for illustration purposes only

**Note: The Autotecnica seats and the 639F adjusters (sliders) are ADR-approved.
We recommend however that the seat conversion is checked by an accredited engineer after fitting the seat or seats to the vehicle.**